

Relevance as Deduction: A Logical View of Information Retrieval

(Abstract)

Gianni Amati
Fondazione Ugo Bordoni
Via B. Castiglione 59, 00142 Roma, Italy
e-mail: gba@fub.it

Konstantinos Georgatos
Dipartimento di Informatica e Sistemistica
Università di Roma "La Sapienza"
Via Salaria 113, 00198 Roma, Italy
e-mail: geo@dis.uniroma1.it

July 19, 1996

The problem of Information Retrieval is, given a set of documents D and a query q , providing an algorithm for retrieving all documents in D relevant to q . However, retrieval should depend and be updated whenever the user is able to provide as an input a preferred set of relevant documents; this process is known as *relevance feedback*. Recent work in IR has been paying great attention to models which employ a logical approach; the advantage being that one can have a simple computable characterization of retrieval on the basis of a pure logical analysis of retrieval. Most of the logical models make use of probabilities or similar belief functions in order to introduce the inductive component whereby uncertainty is treated. Their general paradigm is the following: *find the nature of conditional $d \rightarrow q$ and then define a probability on the top of it*. We just reverse this point of view; *first use the numerical information, frequencies or probabilities, then define your own logical consequence*. More generally, we claim that retrieval is a form of deduction. We introduce a simple but powerful logical framework of relevance feedback, derived from the well founded area of nonmonotonic logic. This description can help us evaluate, describe and compare from a theoretical point of view previous approaches based on conditionals or probabilities.

The first difficulty one encounters towards a logical approach to Information Retrieval is how one should view the algorithm which returns a set of relevant documents. Our proposal is to see such an algorithm as a *proof*. However, this proof is not classical because, as it is widely recognized, $q \rightarrow d$, where q is a query and d a document relevant to q , is not conveyed by the material implication (see [vR86],[vR89]). Also, as the set of data which this proof is based is subject to updating, nonmonotonicity arises. Since there is no need of nesting implications, implication and deduction can be identified and therefore our starting point is to axiomatize a deduction $q \vdash d$. The consequence relation $\vdash$ will reflect the properties that relevance satisfies. A similar approach where nonmonotonic

$\frac{\alpha \vdash \beta}{\alpha \sim \beta}$	(Supraclassicality)
$\frac{\vdash \alpha \equiv \beta \quad \alpha \sim \gamma}{\beta \sim \gamma}$	(Left Logical Equivalence)
$\frac{\alpha \sim \beta \quad \beta \vdash \gamma}{\alpha \sim \gamma}$	(Right Weakening)
$\frac{\alpha \sim \beta \quad \alpha \sim \gamma}{\alpha \sim \beta \wedge \gamma}$	(And)
$\frac{\alpha \sim \beta \quad \alpha \wedge \beta \sim \gamma}{\alpha \sim \gamma}$	(Cut)
$\frac{\alpha \sim \beta \quad \alpha \sim \gamma}{\alpha \wedge \beta \sim \gamma}$	(Cautious Monotonicity)
$\frac{\alpha_0 \sim \alpha_1 \quad \dots \quad \alpha_{n-1} \sim \alpha_n \quad \alpha_n \sim \alpha_0}{\alpha_0 \sim \alpha_n}$	(Loop)
$\frac{\alpha \sim \gamma \quad \beta \sim \gamma}{\alpha \vee \beta \sim \gamma}$	(Or)
$\frac{\alpha \not\sim \neg \beta \quad \alpha \sim \gamma}{\alpha \wedge \beta \sim \gamma}$	(Rational Monotonicity)

Table 1: Rules for Nonmonotonic Inference

consequence relations are used to axiomatize a notion of *aboutness* appears in [BH95]. We shall then show how $\sim$ changes with relevance feedback.

A set of rules for the relevance relation $\sim$ appears in Table 1. This set of rules apart from Rational Monotonicity comprises the system P (see [KLM90]) of *preferential inference*. Preferential inference along with the rule of Rational Monotonicity comprises the system R of *rational inference* (see [LM92]). We propose preferential and rational inference as the simplest and strongest systems axiomatizing the notion of relevance.

However, it is well known that designing a nonmonotonic system is far from trivial. Moreover, nonmonotonicity does not correspond directly to statistical data as statistical operations are in general continuous or monotonic. A solution to this problem is given by a recent characterization of the systems of preferential and rational inference through systems of *monotonic* consequence relations ([Geo96b]) called *priority relations*. A presentation of priority relations follows. Our language of terms will contain only conjunction ($\wedge$). The reason we do not employ a notion of negation is that there is no notion of negation which reflects our intuition in IR. The standard way to look at negation is ruled by the *closed world assumption*: if a term does not occur in a document then its negation occurs. However this makes documents possible worlds and deduction would turn out classical in our model. Hence negation will be replaced by another construction (see below). Documents will be identified with the conjunction of

all terms that occur in them. So, if $\{t_1, \dots, t_n\}$ are all documents occurring in a document d , then $d = t_1 \wedge \dots \wedge t_n$. Our model is based on a recent characterization of nonmonotonicity by the second author through a family of relations among formulas called *priority relations*. A priority relation satisfies

1. $t_1 \vdash t_1$ (Reflexivity)
2. $t_1 \models t_2$ and $t_2 \vdash t_3$ implies $t_1 \vdash t_3$ (Monotonicity)
3. $t_1 \models t_2$ and $t_2 \models t_1$ implies $t_3 \vdash t_1$ iff $t_3 \vdash t_2$, (Logical Equivalence)

where $\models$ is classical. If a priority relation satisfies, in addition,

4. $t_3 \vdash t_1$ and $t_3 \vdash t_2$ implies $t_3 \vdash t_1 \wedge t_2$, (Right Conjunction)
5. $t_1 \vdash t_2$ and $t_2 \vdash t_3$ implies $t_1 \vdash t_3$, (Transitivity)

it will be called *preferential ordering*. If a preferential ordering satisfies, in addition,

6. $t_1 \vdash t_2$ or $t_2 \vdash t_1$ (Connectivity)

it is called *rational ordering*.

We now have the following theorem ([Geo96a],[Geo]): *Preferential and Rational inference relations are generated by preferential and rational orderings, respectively, through a maxiconsistent inference scheme. Moreover, this correspondence is bijective.* This is a powerful machinery for handling nonmonotonic deductions. Once we build a preference (preferential or rational) ordering, we are able to define and compute the associated nonmonotonic consequence relation. Turning conjunction to union of sets of terms the defining conditions of priority relations become:

1. $U \vdash U$ (Reflexivity)
2. $U \subseteq V$ and $U \vdash W$ implies $V \vdash W$ (Monotonicity)
3. $U \vdash V$ and $U \vdash W$ implies $U \vdash V \cup W$, (Right Union)
4. $U \vdash V$ and $V \vdash W$ implies $U \vdash W$, (Transitivity)
5. $U \vdash V$ or $V \vdash U$ (Connectivity)

One can think of these *monotonic* consequence relations as *aboutness* relations. That aboutness should be represented as a monotonic consequence relation appears already in ([HD95]) along with a mix of nonmonotonic rules. Moreover, the above duality theorem translates to the fact that relevance and aboutness are really dual notions. We shall now show how one can easily generate a preferential ordering from frequency information. We show how the user's relevance defines a nonmonotonic consequence relation which is represented by a preferential ordering. In IR, a way to define the informative content of terms is given by the frequencies in the document collection (as in the Robertson Sparck Jones formula): this is enough for us to carry on deductions! A way of constructing a preferential ordering among terms is to divide the set of documents that the user distinguishes into two subsets, the positive set (D^+) and negative set (D^-). Then the set of positive and negative examples will use frequencies to construct two rational orderings. Then these orderings will be combined in a preferential ordering which reflects our intuitions for relevance. Then a document $d = t'_1 \wedge \dots \wedge t'_m$ will be relevant to query $q = t_1 \wedge \dots \wedge t_n$ just in case $t_1 \wedge \dots \wedge t_n \vdash t'_1 \wedge \dots \wedge t'_m$. The construction is the following. Denote with D_t^+ the set of positive relevant documents where t occurs, similarly for the negative case. The frequency of t relative to D^+ is $|D_t^+|$. Now define the following

orderings

$$t_1 \prec_p t_2 \quad \text{iff} \quad |D_{t_1}^+| \leq |D_{t_2}^+|.$$

and

$$t_2 \prec_n t_1 \quad \text{iff} \quad |D_{t_1}^-| \leq |D_{t_2}^-|.$$

It can be shown that $\prec_p$ and $\prec_n$ are rational orderings. Now let

$$t_1 \prec t_2 \quad \text{iff} \quad t_1 \prec_p t_2 \text{ and } t_1 \prec_n t_2.$$

The consequence relation $\prec$ is a preferential ordering. It is now clear that if we perform an update of the sets of positive and negative relevant documents with relevance feedback then $\prec$ changes, too. In particular, this change is *nonmonotonic*.

Consider the following example. The following matrix is the matrix of occurrences between documents d_1, d_2, d_3, d_4 and terms t_1, t_2, t_3, t_4 .

	t_1	t_2	t_3	t_4	
d_1	0	1	0	1	+
d_2	0	1	1	0	+
d_3	0	0	1	1	-
d_4	1	0	0	1	-

We have $t_1 \prec_p \{t_3, t_4\} \prec_p t_2$ and $t_4 \prec_n \{t_1, t_3\} \prec_n t_2$. Thus $t_1 \prec t_3 \prec t_2$ and $t_4 \prec t_2$. For example, $t_3 \wedge t_4 \prec d_1$ and $t_3 \wedge t_4 \prec d_3$, that is the query $t_3 \wedge t_4$ returns d_1 and d_3 as relevant documents, but not d_2 and d_4 . This provides a model for computing the relevance of documents with respect a query on the basis of some evidence.

Consider now a *new* document $d_5 = t_1 \wedge t_2$. We have that d_5 is not totally ranked among the rest of the documents: we can decide just $d_5 \prec d_2$ and $d_4 \prec d_5$. Let U be the number of undecided documents, D_p^+ be the set of positive documents d such that $d \prec d_5$, D_n^- be the set of negative documents d such that $d_5 \prec d$, D_n^+ be the set of positive documents d such that $d_5 \prec d$, and D_p^- be the set of negative documents d such that $d \prec d_5$. If we want to create such a linear ordering among documents we can use the the Robertson Spark Jones' formula and relate it to the number of incomparable documents. Then

$$\frac{N - U}{N} \log \left(\frac{D_p^+ \times D_n^-}{D_p^- \times D_n^+} \right).$$

can be used as a decision rule. In the above example, we get a negative value for d_5 which is then chosen as irrelevant.

A point whose importance should be stressed is that generation of a non-monotonic consequence relation (relevance) through priority relations depends on a notion of negation. Only in presence of negation we are able to define max-consistent inference (see [Geo96b]). We shall now show how a recent approach to IR ([AvRU96]) using expected utility functions defines a natural notion of negation. Suppose that the user supplies two sets of documents representing

positive and negative examples. Through theses sets and the frequencies of terms appearing in those sets one can construct for every term a contingency matrix. Using now *entropy* H and Hintikka's content C , one can define a *weighting* function from the set of terms to the interval $[-1, 1]$. Let w be the weighting function. Set $w(\neg t) = -w(t)$ and $w(t \wedge t') = \min(w(t), w(t'))$. Let

$$r(t) = \begin{cases} w(t) & \text{if } w(t) > 0 \\ 0 & \text{otherwise} \end{cases}$$

The function r *ranks* terms according to their utility. Now the following relation

$$t_1 \vdash t_2 \quad \text{iff} \quad r(t_1) \leq r(t_2)$$

is a rational ordering, and the inference

$$t_1 \vdash t_2 \quad \text{iff} \quad t_1 \wedge t_3 \vdash t_2, \text{ for some } t_3 \not\vdash \neg t_1$$

is a rational *nonmonotonic* inference. The above relation can be readily extend to all boolean combinations of terms. However, we consider only conjunctions of positive terms. Then the rational inference can be effectively checked through the following equivalent definition (t_1 and t_2 are sets of terms)

$$t_1 \vdash t_2 \quad \text{iff} \quad \text{either } t_2 \subseteq t_1, \\ \text{or } t_2 - t_1 \not\vdash \neg t_1.$$

As an example consider three terms t_1 , t_2 and t_3 and their contingency matrices based on a set of 300 relevant documents and a set of 700 irrelevant documents:

	<table><tr><td><i>Rel</i></td><td>$\overline{Rel}$</td></tr><tr><td>0</td><td>300</td></tr><tr><td>626</td><td>74</td></tr></table>	<i>Rel</i>	$\overline{Rel}$	0	300	626	74		<table><tr><td><i>Rel</i></td><td>$\overline{Rel}$</td></tr><tr><td>24</td><td>276</td></tr><tr><td>676</td><td>24</td></tr></table>	<i>Rel</i>	$\overline{Rel}$	24	276	676	24		<table><tr><td><i>Rel</i></td><td>$\overline{Rel}$</td></tr><tr><td>290</td><td>10</td></tr><tr><td>47</td><td>653</td></tr></table>	<i>Rel</i>	$\overline{Rel}$	290	10	47	653
<i>Rel</i>	$\overline{Rel}$																						
0	300																						
626	74																						
<i>Rel</i>	$\overline{Rel}$																						
24	276																						
676	24																						
<i>Rel</i>	$\overline{Rel}$																						
290	10																						
47	653																						
t_1		t_2		t_3																			
$\overline{t_1}$		$\overline{t_2}$		$\overline{t_3}$																			

The weighting function now gives the following

$$\begin{array}{ll} w(t_1) &= -.802 & r(t_1) &= 0 \\ w(t_2) &= -.885 & r(t_2) &= 0 \\ w(t_3) &= .845 & r(t_3) &= .845 \\ w(t_1 \wedge t_2) &= -.885 & r(t_1 \wedge t_2) &= 0 \end{array}$$

We now have $t_1 \vdash t_3$, since $.845 \not\leq .802$, but $t_1 \wedge t_2 \not\vdash t_3$, since $.845 \leq .885$. A table of all possible derivations between terms appears below:

$q \vdash d$	t_1	t_2	t_3	$t_1 \wedge t_2$	$t_1 \wedge t_3$	$t_2 \wedge t_3$
t_1	Y	N	Y	N	Y	N
t_2	N	Y	N	N	N	N
t_3	N	N	Y	N	N	N
$t_1 \wedge t_2$	Y	Y	N	Y	N	N
$t_1 \wedge t_3$	Y	N	Y	N	Y	N
$t_2 \wedge t_3$	N	Y	Y	N	N	Y

This logical framework is just an initial suggestion for future research, which shows that nonmonotonicity, induction and IR can have many common features which are worthwhile to explore.

References

- [AvRU96] G. Amati, C. J. van Rijsbergen, and F. Ubaladini. The maximum expected utility principle and information retrieval. In D.L. Dowe, K.B. Korb, and J.J. Oliver, editors, *Proceedings of the Conference on Information, Statistics and Induction in Science*, pages 129–140, Singapore, 1996. World Scientific Publishing Co.
- [BH95] P. D. Bruza and T. W. C. Huibers. How nonmonotonic is aboutness? Technical Report CS-1995-09, Department of Computer Science, Utrecht University, The Netherlands, March 1995.
- [Geo] Konstantinos Georgatos. Preferential orderings. Typed Manuscript. July 1995.
- [Geo96a] Konstantinos Georgatos. Ordering-based representations of rational inference. In José Júlio Alferes, Luís Moniz Pereira, and Ewa Orłowska, editors, *Logics in Artificial Intelligence (JELIA '96)*, number 1126 in Lecture Notes in Artificial Intelligence, pages 176–191, Berlin, 1996. Springer-Verlag.
- [Geo96b] Konstantinos Georgatos. Expectation relations: A uniform approach to nonmonotonicity. Working Paper 35–96, Dipartimento di Informatica e Sistemistica, Università di Roma “La Sapienza”, November 1996.
- [HD95] T. W. C. Huibers and N. Denos. A qualitative ranking method for logical information retrieval models. Technical Report RAP95-005, Groupe MRIM of the LGI in Grenoble, France, August 1995.
- [KLM90] S. Kraus, Daniel Lehmann, and Menachem Magidor. Nonmonotonic reasoning, preferential models and cumulative logics. *Artificial Intelligence*, 44:167–207, 1990.
- [LM92] Daniel Lehmann and Menachem Magidor. What does a conditional knowledge base entail? *Artificial Intelligence*, 55:1–60, 1992.
- [vR86] C. J. van Rijsbergen. A non-classical logic for information retrieval. *The Computer Journal*, 25(6):481–485, 1986.
- [vR89] C. J. van Rijsbergen. Towards an information logic. In N. J. Belkin and C. J. van Rijsbergen, editors, *Proceedings of the 12th Annual International ACM SIGIR Conference*, pages 77–86, Cambridge, Massachusetts, 1989. ACM Press.